
JE-43PM-Y






We are committed to developing high-quality and highly innovative products while providing the best services to global customers.

Features

- Modular Design
- Touch glass and screen can be independently replaced.
- Uses A-grade LCD panel manufacturer's backlight module panel
- CE/FCC certified



Introuduction

This 43-inch LCD monitor provides a clear 1920x1080 resolution, 250 nits brightness, and a 3000:1 contrast ratio for sharp and detailed display. With an 8ms response time, it supports both VGA and HDMI interfaces for versatile device connectivity. The display offers 16.7 million colors and boasts a 30,000-hour backlight lifespan, ensuring stable performance over extended use. The monitor's plastic frame and metal back shell make it durable and robust, suitable for various environments such as homes and offices. Additionally, it has low power consumption (22W), making it energy-efficient.

Specifications

LCD

Screen size 43"
Screen diadonal 16:9(H:V)
Pixels H x V 1920*1080/60HZ

Visual angle Horizontal (L/R) CR≥10 89 °/89 ° Vertical (up/down) CR≥10 89 °/89 °

Displays the size 940mm (W) \times 529mm (H)

Luminance 250nits
Contrast ratio 3000:1
Response time 8ms
Display plays color 16.7M
Backlight life 30K hours

Interface function

Support interface VGA, HDMI

Sorce

• Input voltage External adapter : 100-240V AC , 50-60 Hz Input voltage range : +12V DC \pm 5%

• Consumption 80W

Material and packaging

Face frame material Sheet metal

Rear shell material
Frame size
Carton size
Sheet metal (Black yarn spray paint)
1021mm (W) x 608mm (H) x 54mm (D)
1126mm (W) × 630mm (H) × 220mm (D)

Weight 28.6 KgAccessories VGA + Adapter

Work environment warranty

• Working temperature 0°C - 40°C

Operating humidity 20% - 80%

• Storage temperature -20°C - 60°C

Store humidity 10% - 90%

Warranty

One year (Except for man-made damage)



Dimensions

